

ARC CL8 PSSR

ARC CLEAR 200 MICRON SECURITY



Overview

Safety and Security Window Films increase the integrity and shatter resistance of glazing. If accidental breakage occurs, glass is held in place - helping to reduce the likelihood of injury.

Increasing the shatter resistance of glazing also increases the difficulty of forced entry - offering better protection against vandals and thieves.

Performance Guide

Energy Savings	☆☆☆☆☆
Heat Rejection	☆☆☆☆☆
Heat Retention	☆☆☆☆☆
Glare Reduction	☆☆☆☆☆
Fade Reduction	☆☆☆☆☆
Safety & Security	☆☆☆☆☆
One Way Privacy	☆☆☆☆☆
Colour	Clear
Installation Position	Internal
Warranty	10 Years

Enhanced Protection

Security can be further improved by using a combination of a Security Window Film and edge retention system. This is recommended for installations for blast mitigation. Various types are available. Speak to your local ARC dealer for further information on a suitable system.

ARC Window Films Ltd

Unit 1, ARC Business Park
Sankey Valley Industrial Estate
Newton-le-Willows
WA12 8AT

T: 0333 800 2400

E: sales@arcwf.com

W: www.arcwindowfilms.com

Data values are representative and are provided for comparative purposes only. To ensure film to glass compatibility and optimum performance, please contact your local ARC representative.

Performance Data

	4mm Single	4/7/6/4mm double
Solar Energy Transmission	77%	64%
Solar Energy Reflection	8%	13%
Solar Energy Absorption	14%	22%
Visible Light Transmission	87%	79%
Visible Light Reflection (Interior / Exterior)	9%	16%
G Value	0.80	0.72
Shading Coefficient (b value)	0.92	0.84
Light to SHG Ratio (LSG)	1.09	1.10
U Value (EN 673 W/m ² k)	5.6	2.7
Emissivity	0.84	0.84
UV Transmission	<1%	<1%
Glare reduction	1%	11%
TSER	20%	28%

Physical Properties

Thickness	224μ
SR Coating	Yes
Tensile Strength	224n/mm ²
Yield Strength	105n/mm ²
Certification	EN 12600 1(B)1